


TVS贴片二极管

TVS SMD DIODE



优良品质 · 诚信经营


一起携手 · 共创辉煌

P4KE Series

产品简介

DESCRIPTION

The P4KE series of high current uni/bi-directional transient suppressors are designed for A.C. line protection and high power DC bus clamping applications. These devices offer uni/bi-directional port protection from 6.8 volts to 400 volts. They provide a clamping voltage lower than the avalanche voltage. Therefore, any voltage rise due to increased current conduction is contained to a minimum, providing the best possible protection level. They can also be connected in series and/or parallel to create very high capacity protection solutions.



产品特征

FEATURES

- Low zener impedance.
- Excellent clamping capability.
- Repetition rate (duty cycle): 0.01%.
- JEDEC DO-41/DO-204AL Molded Plastic.
- Color band denoted cathode except bidirectional.
- High temperature soldering: 260°C/10s at terminals.
- Glass passivated chip junction in DO-41/DO-204AL package.
- 400W Peak Pulse power capability at 10x1000μs waveform.
- Fast response time: typically less than 1.0ps from 0V to V_{BR} min.

绝对最大额定值
ABSOLUTE MAXIMUM RATINGS

 (T_A=25°C, RH=45%-75%, unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak Pulse Power dissipation on 10/1000μs waveform	P _{PP}	400	W
Peak pulse current of on 10/1000μs waveform	I _{PP}	See next Table	A
Steady state power dissipation at T _L =75°C	P _{M(AV)}	1.0	W
Operating junction and Storage temperature range	T _{STG} , T _J	-55 to +150	°C
Peak forward surge current, 8.3ms single half sine-wave	I _{FSM}	40	A

电气特性
ELECTRICAL CHARACTERISTICS

 T_A = 25°C

Part Number		V _R	I _R @ V _R	V _{BR} @ I _T		I _T	V _C @ I _{PP}	I _{PP} ^③
Uni-Polar	Bi-Polar	V	μA	Min(V)	Max(V)	mA	Max(V)	A
P4KE6.8A	P4KE6.8CA	5.8	150	6.45	7.14	10	10.5	38.1
P4KE7.5A	P4KE7.5CA	6.4	100	7.13	7.88	10	11.3	35.4
P4KE8.2A	P4KE8.2CA	7.02	50	7.79	8.61	10	12.1	33.1
P4KE9.1A	P4KE9.1CA	7.78	20	8.65	9.55	1	13.4	29.9
P4KE10A	P4KE10CA	8.55	10	9.50	10.50	1	14.5	27.6
P4KE11A	P4KE11CA	9.4	5	10.50	11.60	1	15.6	25.7
P4KE12A	P4KE12CA	10.2	2	11.40	12.60	1	16.7	24
P4KE13A	P4KE13CA	11.1	1	12.40	13.70	1	18.2	22
P4KE15A	P4KE15CA	12.8	1	14.30	15.80	1	21.2	18.9
P4KE16A	P4KE16CA	13.6	1	15.20	16.80	1	22.5	17.8
P4KE18A	P4KE18CA	15.3	1	17.10	18.90	1	25.2	15.9
P4KE20A	P4KE20CA	17.1	1	19.00	21.00	1	27.7	14.5
P4KE22A	P4KE22CA	18.8	1	20.90	23.10	1	30.6	13.1
P4KE24A	P4KE24CA	20.5	1	22.80	25.20	1	33.2	12.1
P4KE27A	P4KE27CA	23.1	1	25.70	28.40	1	37.5	10.7
P4KE30A	P4KE30CA	25.6	1	28.50	31.50	1	41.4	9.7
P4KE33A	P4KE33CA	28.2	1	31.40	34.70	1	45.7	8.8
P4KE36A	P4KE36CA	30.8	1	34.20	37.80	1	49.9	8.1
P4KE39A	P4KE39CA	33.3	1	37.10	41.00	1	53.9	7.5
P4KE43A	P4KE43CA	36.8	1	40.90	45.20	1	59.3	6.8
P4KE47A	P4KE47CA	40.2	1	44.70	49.40	1	64.8	6.2
P4KE51A	P4KE51CA	43.6	1	48.50	53.60	1	70.1	5.8

$T_A = 25^\circ\text{C}$, continued

Part Number		V_R	$I_R @ V_R$	$V_{BR} @ I_T$		I_T	$V_C @ I_{PP}$	$I_{PP}^{\text{①}}$
Uni-Polar	Bi-Polar	V	μA	Min(V)	Max(V)	mA	Max(V)	A
P4KE56A	P4KE56CA	47.8	1	53.20	58.80	1	77.0	5.2
P4KE62A	P4KE62CA	53.0	1	58.90	65.10	1	85.0	4.8
P4KE68A	P4KE68CA	58.1	1	64.60	71.40	1	92.0	4.4
P4KE75A	P4KE75CA	64.1	1	71.30	78.80	1	103.0	3.9
P4KE82A	P4KE82CA	70.1	1	77.90	86.10	1	113.0	3.6
P4KE91A	P4KE91CA	77.8	1	86.50	95.50	1	125.0	3.2
P4KE100A	P4KE100CA	85.5	1	95.00	105.0	1	137.0	3.0
P4KE110A	P4KE110CA	94.0	1	105.0	116.0	1	152.0	2.7
P4KE120A	P4KE120CA	102.0	1	114.0	126.0	1	165.0	2.5
P4KE130A	P4KE130CA	111.0	1	124.0	137.0	1	179.0	2.3
P4KE150A	P4KE150CA	128.0	1	143.0	158.0	1	207.0	2.0
P4KE160A	P4KE160CA	136.0	1	152.0	168.0	1	219.0	1.9
P4KE170A	P4KE170CA	145.0	1	162.0	179.0	1	234.0	1.8
P4KE180A	P4KE180CA	154.0	1	171.0	189.0	1	246.0	1.6
P4KE200A	P4KE200CA	171.0	1	190.0	210.0	1	274.0	1.5
P4KE220A	P4KE220CA	185.0	1	209.0	231.0	1	328.0	1.3
P4KE250A	P4KE250CA	214.0	1	237.0	263.0	1	344.0	1.2
P4KE300A	P4KE300CA	256.0	1	285.0	315.0	1	414.0	1.0
P4KE350A	P4KE350CA	300.0	1	332.0	368.0	1	482.0	0.9
P4KE400A	P4KE400CA	342.0	1	380.0	420.0	1	548.0	0.8

① Surge waveform: 10/1000 μs

V_R : Stand-off Voltage -- Maximum voltage that can be applied

V_{BR} : Breakdown Voltage

V_C : Clamping Voltage -- Peak voltage measured across the suppressor at a specified I_{PP}

I_R : Reverse Leakage Current

额定值和 V-I 特性曲线

RATINGS AND V-I CHARACTERISTICS CURVES

$T_A=25^{\circ}\text{C}$, unless otherwise noted

Fig.1: V-I curve characteristics (Uni-directional)




Fig.2: V-I curve characteristics (Bi-directional)




Fig.3: Pulse waveform





Fig. 4 Pulse derating curve





焊接参数

SOLDERING PARAMETERS


Reflow Condition		Pb-Free assembly (see FIG.5)
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150°C
	-Temperature Max($T_{s(max)}$)	+200°C
	-Time (Min to Max) (t_s)	60-180 secs.
Average ramp up rate (Liquid us Temp (T_L) to peak)		3°C/sec. Max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature(T_L)(Liquid us)	+217°C
	-Temperature(t_L)	60-150 secs.
Peak Temp (T_p)		+260(+0/-5)°C
Time within 5°C of actual Peak Temp (t_p)		30 secs. Max
Ramp-down Rate		6 °C/sec. Max
Time 25°C to Peak Temp (T_p)		8min. Max
Do not exceed		+260°C

Fig. 5 Reflow condition



标记和订购信息
MARKING & ORDERING INFORMATION


- | | | | |
|------|-----|-----|-----|
| P4KE | XX | C | A |
| (1) | (2) | (3) | (4) |
- (1) Series:400 watts series
 (2) Reverse Stand-off Voltage
 (3) Bi-directional
 (4) 5% V_{BR} Voltage tolerance

机械数据
PACKAGE MECHANICAL DATA


Ref.	Dimensions			
	Inches		Millimeters	
	Min.	Max.	Min.	Max.
A	1.000	-	25.40	-
B	0.193	0.209	4.90	5.30
C	0.027	0.035	0.69	0.89
D	0.095	0.110	2.40	2.80

Part Number	Case Type	Quantity	Packing Option
P4KEXXCA/A	DO-41/DO-204AL	2000	Box